

## mc50 System

The mc50 comes with the KK55SL, which can pass through 90° bends from 4" onwards and inspect pipe diameters up to 16" with the optional large roller upgrade. Includes 512 Hz sonde.

### System Specifications

- 200 ft. (60m) of 9.2mm fiberglass push cable (up to 260 ft.)
- 512 Hz sonde standard (33 kHz special order)
- Electronic on-screen distance counter
- Lithium Ion battery for more than 1.5 hours operation
- Power Supply: 100 - 240V AC; 12V DC Car adapter
- Lightweight stainless steel and carbon reel cage
- Control unit: On/off switch, light regulation, distance counter reset, battery level LEDs, BNC video out
- Mechanical reel brake
- Weight: 35 lbs.; Dimensions: 25" x 26" x 12" (L x H x W)



## Monitor & Recording

- 8.4" TFT LCD sunlight readable, records video, voice and photo
- Pelican® Storm Case heavy-duty housing
- Ergonomically attached to reel
- SD card reader, max 32 GB for approx. 20 hours of video
- MPEG-4 Video (.avi, 800x600); Pictures (.bmp 640x480)
- Integrated Qwerty keyboard available (special order)

### KK55SL Auto-Upright Camera

Range	3" - 16" (70-400mm)
Video Quality	High-resolution 480 TVL
Lighting	16 pcs LEDs
Lens	4mm sapphire glass
Water Tight	Up to 145 psi
Outer diameter	2.17" (55mm)
Cylindrical length	1.42" (36mm)

