

**Sanitary  
Equipment  
Co., Inc.**

# SALES PARTS SERVICE

**DO IT RIGHT THE FIRST TIME**

Committed to delivering equipment that meets immediate needs and exceeds expectations for years to come.

## INDUSTRY LEADING EQUIPMENT



**SHOP OEM PARTS AT [SANITARYEQUIPMENT.COM](http://SANITARYEQUIPMENT.COM)**

25 Industry Dr  
West Haven, CT 06516  
(203) 933-9599

1140 Turnpike St., Unit 3&4  
Stoughton, MA 02072  
(855) 373-7324



## TMAX™ 2

Heavy-duty work requires a reliable, heavy-duty mechanic truck, and that describes the TMAX 2 to a T. Like all Stellar equipment, the TMAX 2 begins with professional engineering and top-quality materials. Add in precision construction, and it's no wonder the TMAX 2 Mechanic Truck has a reputation as a durable workhorse.

[Customer Story](#): See why “Gold Rush: Dave Turin’s Lost Mine” chooses Stellar.



## ADDITIONAL INFORMATION

The TMAX 2 is available in aluminum in multiple configurations, including a design for a low cab-forward (LCF) chassis. For added capabilities and convenience, the crane pedestal/compartments is constructed of steel material capable of handling the robust lifting capacity of Stellar cranes equipped with CDTpro™ control systems while providing the same storage space as other, non-reinforced compartments.

### **New Features for 2025 TMAX Models:**

- Mounting rails integrated within compartments allow for fully customizable configurations.
- Ease of wiring access with added pre-drilled holes between compartments for seamless wiring installation.
- Easily add a wide range of mechanic service truck accessories, like bale-handle drawer sets and bolt bins for better organization.
- Hydraulic reservoir design features a top-mounted filter for easier maintenance.
- Simplified back-end design minimizes welded holes on the truck body for improved performance.
- Mudflaps positioned to wire guards to avoid interference with exhaust systems.

### **Proven Performance:**

- Available in either 11' or 14' bodies.
- Stellar's torq-isolator crane support design isolates the crane compartment from the rest of the side pack.
- Lifting stresses are transferred to the stabilizers and box-type subframe, not the compartment doors.
- Aluminum extruded top with drill-free mounting rails make it easy to add a wide range of mechanic service truck accessories.
- Aluminum sidepack and doors reduce weight and corrosion, allowing for more payload and longer life.
- Bodies feature a 21" or 30" steel workbench bumper with an integrated full-width long bar storage compartment and vise mounts.
- Roller-type boom support helps center the crane boom when stowing.
- Stainless-steel billet-style hinges have hidden fasteners and a rugged 5/16" stainless-steel rod for years of heavy use.
- Rotating master-lock system for security.
- Exterior mounted light box provides easy mounting for work lights and other accessories while minimizing entry points into the body.
- 3-point compression latches keep weather-stripping tight while allowing easy access.
- Double-panel 1/8" aluminum tailgate with hinged arm brackets provides a stout working surface.

- 250-lb capacity, adjustable divider shelves made of spangled galvanized steel.
- Complete undercoating, with minimum of 6.5 mils of petroleum base material, provides extra protection from corrosion and road debris.
- Easily add a wide range of mechanic service truck accessories.

#### **Models:**

- TMAX 2-11
- TMAX 2-14
- TMAX 2-14 Low Cab-Forward

#### **Store Your Long Chains & Tools**

With the pull-out drawer on our innovative Workbench Bumper Drawer System, you get lockable storage space for chains, long tools and more. [Contact](#) our sales team for details.

#### **Works With CDTpro™ Control System**

Several cranes compatible with the TMAX 2 feature the new [CDTpro Control System](#). Its innovative, industry-only Range Finder™ technology provides real-time max lifting capacity from any point as you walk around the crane.

# SPECIFICATIONS

	TMAX 2-11	TMAX 2-14	TMAX 2-14 Low Cab-Forward
<b>Applicable Chassis:</b>	25,500 – 33,000 GVWR (22.5 tire size)	25,500 – 33,000 GVWR (22.5 tire size)	25,500 – 33,000 GVWR (22.5 tire size)
<b>Body Height:</b>	60" (152 cm)	60" (152 cm)	60" (152 cm)
<b>Body Width:</b>	94" (239 cm)	94" (239 cm)	94" (239 cm)
<b>Floor Width:</b>	50" (127 cm)	50" (127 cm)	50" (127 cm)
<b>Compartment Depth:</b>	22" (56 cm)	22" (56 cm)	22" (56 cm)
<b>Clear Cab to Axle:</b>	84" (213 cm)	120" (305 cm)	120" (305 cm)
<b>Body Length:</b>	133" (338 cm)	169" (429 cm)	169" (429 cm)
<b>Net Weight:</b>	Aluminum: 3,459 – 3,544 lbs (1,569 – 1,607 kg) Steel: 4,388 – 4,469 lbs (1,991 – 2,027 kg)	Aluminum: 3,960 lbs (1,797 kg) Steel: 5,140 lbs (2,332 kg)	Aluminum: 3,665 lbs (1,662 kg)

# COMPATIBLE CRANES

	Crane Rating	Max. Reach	Max. Capacity	Control Systems
<b>Hydraulic Cranes</b>				
<b>7621</b>	44,840 ft-lb*	21' (6.40 m)	7,500 lbs (3,402 kg)	CDTpro™
<b>7630</b>	44,840 ft-lb*	29' 8" (9.04 m)	7,500 lbs (3,402 kg)	CDTpro™
<b>8621</b>	53,100 ft-lb*	21' (6.40 m)	8,600 lbs (3,900 kg)	CDTpro™
<b>8630</b>	53,100 ft-lb*	29' 8" (9.04 m)	8,600 lbs (3,900 kg)	CDTpro™
<b>10621</b>	70,800 ft-lb*	21' (6.40 m)	10,000 lbs (4,082 kg)	CDTpro™
<b>10630</b>	70,800 ft-lb*	29' 9" (9.07 m)	10,000 lbs (4,082 kg)	CDTpro™
<b>12621</b>	77,800 ft-lb*	21' (6.40 m)	12,000 lbs (5,443 kg)	CDTpro™
<b>12630</b>	77,800 ft-lb*	29' 9" (9.07 m)	12,000 lbs (5,443 kg)	CDTpro™



**Sanitary  
Equipment  
Co., Inc.**

# SALES PARTS SERVICE

DO IT RIGHT THE FIRST TIME

Committed to delivering equipment  
that meets immediate needs  
and exceeds expectations  
for years to come.

## INDUSTRY LEADING EQUIPMENT



SHOP OEM PARTS AT [SANITARYEQUIPMENT.COM](http://SANITARYEQUIPMENT.COM)

25 Industry Dr  
West Haven, CT 06516  
(203) 933-9599

1140 Turnpike St., Unit 3&4  
Stoughton, MA 02072  
(855) 373-7324