HAD-200-120-54 20,000 lbs. Capacity

PALFINGER HOOKLIFT





STANDARD FEATURES INCLUDE:

- Available with 54" hook height
- 14ft Containers
- 12ft Containers with an 18,500 loading capacity

The PALFINGER Principle

PALFINGER HOOKLIFT

Omaha Standard Inc. P.O. Box 5757 Trenton, NJ 08638



Corporate Office: (203) 933-9599 25 Industry Drive, West Haven, CT, 06516


14

MA location:


(855) 373-SECI 1140 Turnpike Street, Unit 3 & 4, Stoughton, MA, 02072

14






MAX. LOAD ANGLE 32 DEG



MAX. LOAD ANGLE 31 DEG



MAX. DUMPING ANGLE 58 DEG

FEATURES:

- 20,000 LBS capacity
- High dump, ``True Dump Truck" style dumping dual pivot
- Designed and manufactured in the United States
- Low pressure 2800 PSI hydraulics easily adapts to hydraulic based accessories .
- Dual lift cylinders for added strength and stability .
- Sliding jib to accommodate short containers and adjust the weight distribution . .
- Dual rear rollers side for easy container movement
- Poly fenders with full width bumper .
- LED stop, turn and marker lights with factory plug-in harness
- Pintle hook mounting plate is standard
- Patented floating jib eliminates all electromechanical controls and allows the body toDump bodies (standard & heated) be slid back during the dump mode
- US manufactured pump, valve, cylinders and fittings
- All models include an A-frame drawing

MAX. DUMPING ANGLE 58 DEG

CUSTOMIZED QUICK CHANGE BODIES:

- Open top containers
- Closed storage bodies
- Salt and sand spreaders
- Tree spraying units .
- Septic cleaning pumps
- Hydroseeders
- Concrete forms
- Scaffold delivery skids
- **Recycling containers**
- Flatbed bodies
- Water tanks
- Spraying systems
- Liftgate bodies
- Cranes: skid mounted
- Bark mulch blowers
- **Contractor bodies**



Applications shown in the leaflet do not always correspond to the standard specifications. Design and specification are subject to change without prior notice.